## **EQUIPMENT TRAILER 14K SERIES**



#### **Features & Benefits**

#### 1. Manual Lock System:

Located on side rail where deck split occurs.

#### 2. Safety Cables & Break Away Kit:

Connected to vehicle and crossed under the hitch. Breakaway kit will bring trailer safely to a stop by activating brakes should disconnect from tow vehicle occur during transit.

#### 3. Tongue:

6 inch aluminum tube frame construction for increased strength and robust usage.

#### 4. Lights & Electrical:

All weather sealed connectors to prevent corrosion. Standard LED lighting throughout and RV Style 7-way plug for tow vehicle connection.

#### 5. Side Rails & Decking:

Extruded lightweight aluminum construction with no structural welds gives more strength, lower empty weight and higher payload.

#### 6. Fixed 7k Rubber Torsion Axle Suspension:

Provides even weight distribution, durability, and decreased tire wear.

#### 7. Tires & Wheels:

16" premium aluminum wheels and ST235/80R16 tires.

#### 8. Hydraulic Split Tilt Deck:

Adjustable hydraulic system allows for controlled raising and lowering of deck when loading/unloading equipment. 12 degree loading angle.

# ENHANCED INNOVATION IN EQUIPMENT TRANSPORTATION







**14K SERIES** Equipment Trailers

Model	GVW	<b>Usable Deck Size</b>	Empty Weight
1420	14,000	16' + 4' x 82-3/8"	Est. 2,680 lbs
1424	14,000	18' + 6' x 82-3/8"	Est. 3,000 lbs

# Standard Specifications

	1420	1424
Overall Width	102"	102"
Overall Length	24′ 6″	28' 6"
Stationary Deck Length	4′	6'
Tilt Deck Length	16'	18'
Tongue Length	56"	56"
Deck Height	22"	22"
Loading Angle	12°	11.5°
Wheel Size	16"	16"
Tire Size	ST235/85R16	ST235/85R16
Axle	Fixed	Fixed
Suspension	Rubber Torsion	Rubber Torsion
Brakes	Electric Self-Adjusting	Electric Self-Adjusting
Coupler	2-5/16"	2-5/16"
Coupler Position	Adjustable	Adjustable
Jack Style	Side Crank	Side Crank
Jack Rating	12,000 lbs.	12,000 lbs.
Stake Pockets	18	18
Lighting	LED	LED

### **Accessories**

- Spare Tire
- Spare Tire Mount
- Toolbox

